

## Lagging Kit Request Form

To ensure the correct lagging kit is quoted and supplied, please fill out the following. Required fields have a **red border** and are denoted with an **'\*'**.








Name:

Company:

Email:

Location:

Phone:

- |                                |   |   |    |
|--------------------------------|---|---|----|
| 1. Belt Width                  |   | Inches  | MM |
| 2. Pulley Face Width           |   | Inches  | MM |
| 3. Pulley Diameter             |   | Inches  | MM |
| 4. Lagging Type Preference     | Ceramic   | URDS (Rubber Modified Diamond pattern)  |    |
| 5. Lagging Face Preference     | Ceraflex 1/2" (12.5mm )<br>3/4" x 3/4" inline tiles                                 | URDS 5/8" (15mm)  |    |
|                                |   |   |    |
|                                | Ceratax 5/8" (15mm)<br>1" x 1" staggered tiles                                      | URDS-SP 1/2" (12.5mm)   |    |
|                                |  |  |    |
| 6. Lagging Thickness           |   | Inches  | MM |
| 7. Cold Bond Cement & Hardener | SA 2000+  | SA 4000+  |    |
|                                |  |  |    |
|                                | ECRF  |    |    |
| 8. Additional Comments         |   |   |    |



Please send the completed form to [laggingkits@almex.com](mailto:laggingkits@almex.com), or call 1-800-Y-SPLICE or your local Almex Sales Rep.