


COREPEL.COM

ESSENCE

CO RE PEL

EXTRA-DURABLE WATERPROOF FLOOR



UNBEATABLY DURABLE
THE CORE
THE FLOOR
ESSENCE BALANCE
ESSENCE GO
FACTS

CONTENTS

ESSENCE



UNBEATABLY DURABLE

UNBEATABLY DURABLE


Our everyday lives are full of the hustle and bustle of different activities. So it's all the more important that we have resilient flooring that keeps pace with all our needs. A Corepel floor effortlessly rises to the challenge.

A Corepel resilient floor can withstand whatever life throws at it – children playing, pets romping around, objects falling – and still maintains its beauty.

With its Enhanced Wood Core embedded in high-performance resin, it is dimensionally stable, waterproof and resistant to scratches and dents.


The high share of wood contained in Corepel's core is exclusively from certified and controlled sources. And it's the first floor ever to meet the requirements set out in the DEC standard.

Corepel: the right choice for the long run.



ESSENCE

UNBEATABLY DURABLE



UNBEATABLY DURABLE

5X STRONGER

Let the sunlight in and enjoy the warmth – a Corepel floor retains its shape under any condition.


Corepel's floor panels fit together as seamlessly as the pieces of a puzzle. To ensure that this remains the case even when temperatures fluctuate, its wooden core is embedded in heat-resistant resin, alltogether creating a bond between panels that is five times stronger than other designer floors.

Even when exposed to moisture and high loads, the joints between the panels hold tight. Even an uneven subfloor is no problem for Corepel. Its surface stays smooth and beautiful.

So, what are you waiting for? Open the curtains and let the sunshine in – even if you have floor-to-ceiling windows.

Corepel always retains its form and elegance.

ARTRA



100% WATERPROOF

There's no need to worry if Corepel ends up covered in splashes and drips – it's waterproof.





Whether Trixie's had a little accident or someone's spilled a soft drink, all kinds of puddles can quickly cause a wooden floor to warp. But that's not the case with Corepel.

Have your children come running indoors, still wearing their soaking-wet shoes, after the heavens opened? That's not a problem! Corepel's tight joints don't let the slightest drop of moisture through.

Corepel Essence floors are even suitable for use in bathrooms and laundry rooms. They don't swell or absorb odors. Quite the contrary. They are easy to steam clean or wet mop

Because 100% waterproof also means 100% practical.

ESSENCE

UNBEATABLY DURABLE

EXTREMELY ROBUST

Corepel fits in with your active life. In all the rooms that are at the heart of the home.

Martindale test The Martindale method is used to simulate the conditions created by children or pets running around on a floor thousands of times over. Corepel Essence proved its extreme scratch resistance and achieved an excellent MSR A2 rating (EN 16511:2019) during this test.

Taber test


Taber test During the Taber test, a product's abrasion resistance is tested by using falling sand in a targeted manner. Corepel Essence was still as flawlessly beautiful after 8,000 cycles as it was at the beginning. Its impressive quality corresponds to Use Class 33 (EN 16511:2019).

D40472 MORGAN OAK SILVER ESSENCE BALANCE

Sharp edges can do a great deal of damage to floor coverings. But Corepel has is perfectly protected. Thanks to its extraordinary abrasion resistance, soccer boots or surfboards leave just as few traces as animal claws or exercise machines.

Corepel adds a brilliant touch to all hightraffic areas of the home – from the hall to the wet room. And, since it is resistant to the heat and cold, it is also an ideal choice for kitchens or conservatories.

Live life the way you want to. Your Corepel resilient floor will remain intact and beautiful – every time it is used.



ESSENCE

THE CORE

ENCAPSULATED WOOD CORE

In the same way that an oyster shell provides a protective casing for the pearl inside, a shell of high-performance resin protects Corepel's wooden core too.

The Corepel core consists of natural wood, which is encased in protective high-performance resin. That's why Corepel can withstand intense home workouts, stomping children and falling household items – in short, any challenge that you might encounter in your everyday family life.

As unyielding as Corepel is in the face of adverse influences, it has just as gentle an impact on the environment. The wood used in Corepel floors is exclusively FSC/PEFC-certified.

And the fact that Corepel has been awarded labels such as FloorScore, Greenguard Gold, VOC A+ and CARB/ TSCA clearly illustrates that it is manufactured as part of an amazingly low-emission production process and ensures highest indoor air quality.



19.50

A TOUGH PER-FORMER GENTLE WITH NATURE

Corepel Essence is the most classic of our design floorings. Its core contains a large share of natural wood from certified sources only. Encased in protective high performance resin it provides enhanced stability.

> D80622 NORFOLK OAK BRONZE ESSENCE BALANCE

ESSENCI

DURABLE ECO COMPOSITE THE NEW STANDARD

Corepel is particularly durable and equally eco-friendly, containing a high share of wood exclusively from FSC/PEFC-certified sources. It is the first flooring ever to meet the requirements set out in the new DEC standard and is therefore classed as a Durable Eco Composite.

D80582 NORFOLK OAK BEIGE ESSENCE BALANCE



ESSENCE

an distanting of the succession of the succession of

GREAT METERS AND A

Calebian III distance

Caracteristics

ESSENCE BALANCE THE SMART CHOICE

Who says you can't be soft and strong at the same time? Corepel Essence floors certainly are.

Coated with a SOFT SHIELD film, Smart Line features a very soft feel in a highly durable floor. The film makes for a smooth touch underfoot and an attractive matte finish.

Authentic in both materials and appearance, Smart Line closely emulates the natural elements. Those natural good looks hold up over time – no matter the wear and tear. Wood-fiber based, the floors are protected against fungi and moisture. With the ability to ward off abrasion, Smart Line achieved class 33 rating after testing. And though they look slick, the floor has proven slip resistant qualities, with class R10 rating. A lifetime residential ensures Corepel remains your floor for life (15 year commercial warranty).

Perfect for use in multi-family residences or open-plan rooms with high ceilings, Smart Line is quiet as a mouse. Equipped with an Eco Sound Hydro underlay, it is optimized to keep noise to a minimum. Its impact sound reduction reaches up to 21 decibels. A 5G click system makes for easy and fast installation. Corepel Essence floors are available in 5 formats:


WOOD STANDARD 1380 x 195 x 6,5 mm 54.33" x 7,68" x 6,5 mm

WOOD OVERSIZE 1845 x 244 x 7.5 mm 72.63" x 9.6" x 7.5 mm

WOOD OVERSIZE+ 2025 × 244 × 8 mm 79.7" × 9.6" × 8 mm

STONE OVERSIZE 1380 x 396 x 7.5 mm 54.33" x 15.59" x 7.5 mm

WOOD HERRINGBONE 665 x 133 x 4.3 mm 26.2" x 5.2" x 4.3 mm




ESSENCE BALANCE VOOD EDITION STANDARD

With its authentic wood look, standard-format Balance Wood pairs down-to-earth robustness with aesthetic visual appeal.

D40482 MORGAN OAK BROWN ESSENCE BALANCE

ESSENCE

ESSENCE BALA












DISCREETLY ELEGANT



DEKORE













The standard-format panels set the scene for tastefully furnished interiors. They pair beautifully with Scandi-style furnishing and selected design classics alike. Balance Wood Standard's gorgeous wood look creates a neutral foundation that ties any space together.

ESSENCE





The standard-format panels set classics alike. Balance Wood Stanthe scene for tastefully furnished interiors. They pair beautifully with Scandistyle furnishing and selected design together.

dard's gorgeous wood look creates a neutral foundation that ties any space

ESSENCE BALANCE WOOD EDITIO

The elegant oversized format brings a sense of sumptuousness and chic to your space.

4550 CRYSTAL OAK BLOND GREY ESSENCE BALANCE


22

ROY JACOBSEN

ESSENCE

ESSENCE BALANCE WOOD EDITION | OVERSIZE

0







AN IDEAL AESTHETIC



DECORS









The beautiful synchronous structures look at least as good as real wood. The pattern only repeats itself every24 panels, so the flooring has a calm, natural look – perfect for infusing the space with your own personal style.





Pair XL Wood with unusual and exciting interiors. Pampas grass, polished vases and pops of color contrast the calm created by the floor. Or add this

clean and contemporary floor to a room with tradititional decorative elements like skirting to accent the extraordinary.

ESSENCE BALANCE STONE EDITION OVERSIZE


Stone decors in an oversized format give your space a clean, pared-back look.

48 MARMOR ROMEO WHITE SENCE BALANCE

ESSENCE

STONE EDITION | OVERSIZ

SSENCE BALA





ESSENCE BALANCE | STONE EDITION | OVERSIZE

ESSENCE

STRIKING BALANCE



30







A nice, neutral backdrop. Balance Oversize in Stone decor gets it just right: Not too much, not too little. Harmonious and peaceful, the authentic stone appearance grounds the interior. It strikes the right balance, even in a busy room.



4448 MARMOR ROMEO WHITE ESSENCE BALANCE 11



Create an oasis of calm in any room with a pared down decor. XL Stone provides the foundation for a place of focus and concentration, filled only with the bare essentials. Porcelain fixtures and heavy wood accentuate the natural look of the stone.


ESSENCE BALANCE WOOD EDITION OVERSIZE+ ESSENCE

For rooms where you can really relax: oversized panels.

WOOD EDITION | OVERSIZE

ESSENCE BALANCE

80071 MOLINO MELANGE ESSENCE BALANCE





EXTRA STYLISH





DEKORE










Balance Oversize+ boasts tiles with even greater length and width. This oversized format speeds up laying and ensures a stylish look. Thanks to their synchronous structures, the panels feature a distinctive, natural-looking wood texture. The grain only repeats itself every 16 tiles.

80071 MOLINO MELANGE ESSENCE BALANCE Pr

6.6

T-4-



ESSENCE BALANCE | WOOD EDITION | OVERSIZE+

ESSENCE


Balance Oversize+ in wood decor offers abundant natural style, coupled with all the robustness and water resistance of a typical Corepel floor. Perfect for taking on everyday life! ESSENCE

ESSENCE GO | HERRINGBONE

ESSENCE GO WOOD EDITION HERRINGBONE

Corepel Essence Go is a stunning sight with its timeless herringbone look. The panels are on the thicker side and are glued when they are laid. As such, Corepel Essence Go forgives any minor bumps on the subfloor and minimizes preparation time when laying.

D80612 NORFOLK OAK COFFEE ESSENCE GO





D80592 NORFOLK OAK



A STRONG CHARACTER





ESSENCE

ESSENCE GO | HERRINGBONE



Two new variants of synchronous structures with an authentic wood texture offer a delightful look and feel. The panels can be laid geometrically like real parquet and glued to the subsurface. They are also suitable for large areas and commercial premises.

43

D40452 MORGAN OAK TOFFEE ESSENCE GO

1



EV S

The herringbone pattern looks both classic and elegant. This is a floor perfect for any style of interior design.



ESSENCE



Corepel Essence Go is the perfect floor covering for rooms of all types and dimensions. Enjoy the look of herringbone flooring, with the added functionality and robustness that only Corepel can offer. Corepel Essence Go is the perfect floor covering for rooms of all types and dimensions. Enjoy the look of herringbone flooring, with the added functionality and robustness that only Corepel can offer.

FACTS

ESSENCE

ESSENCE			
class of usage			16511:2019
thickness		ΕN	16511:2019
width			16511:2019
length		ΕN	16511:2019
pcs/box			
surface area per box			
box/pallet			
weight/box			
weight/pallet			
warranty residential (as per separate w https://www.corepel.com/en/service/			
warranty commercial (as per separate https://www.corepel.com/en/service/			
surface layer			
unique plank design			
domestic usage interior use			
commercial usage interior use			
waterproof			
type of installation			
surface without transition moldings			
post installation temperature range			
type of edge			
	CE		13501:2010
floor heating	CE		
thermal resistance	CE		
antistatic	CE	EN	1815:2011
formaldehyde emission	CE		717-1:2005
slip resistance	CE	ΕN	14041:2008
slip resistance	CE	DIN	1 51130:2014
abrasion resistance (falling-sand meth	od)	EN	16511:2019
micro-scrartch resistance			16511:2019
impact resistance large ball			16511:2019
resistance to indentation			24343-1:2012
stain resistance			438-2:2019
			24334:2019
strength of joint (short side/long side)		150	24334.2019
gloss level			
light fastness			20105:1995
castor chair resistance			425:2002
burning cigarette			1399:1998
antibacterial resistance		ISC	22196:2011
sustainable certification			
VOC emission		ISC	16000
natural wood fiber content			
PVC free			
heavy metal content		AS	TM F963
attached underlayment			
impact sound transmission		AS	TM E492 IIC
airborne sound transmission			TM E90 (STC)
effectiveness of floor coverings in reducing impact sound transmission			TM E2179 elta IIC)

BALANCE|WOODEDITION|STANDARD

BALANCE WOODEDITION STANDARD
class 33
5.5 mm, 0.21 in.
1380 mm, 54.33 in.
10
2.69 m², 28.96 sqft
40
17.38 kg, 38.32 lbs
720 kg, 1587 lbs
limited lifetime
Soft Shield
10
for example: floor, kitchen, living room, home office, bathroom
for example: classroom, offices, stores
100% waterproof
5G Click
20 x 20 m, 65 x 65 ft (using state of the art technology) -34°C to +70°C, -30°F to +160°F
V-groove 4 sided
B _{fi} -s1, flame retardant, no/low smoke emission
embedded (liquid based) radiant floor heating
max. 0.1 (m2K)/W
≤ 2 kV
Class E1/2020, under detection limit (CARB2/TSCA VI compliant)
DS R10
IP ≥ 8000, class 34
MSR-A1
> 1800 mm/ 70.86 in., class 34
≤ 0.15 mm/ 0.005 in.
No visible change (aceton, coffee, hydrogen peroxide)
3x higher than Class 34 (11.28 kN/m)
4 points, matt oiled look
light fast, ≥ 6
25,000 cycles without any damage
yes, highly resistant
antibacterial
VOC A+, agBB schema, Floorscore, Greenguard Gold
Core Board more than 50 %
yes
yes
pass (>0.25 ppm)
1 mm ECO SOUND HYDRO approx. 68 dB (thanks to ECO SOUND HYDRO underlay)
approx. 68 dB (thanks to ECO SOUND HYDRO underlay) approx. 63 dB (thanks to ECO SOUND HYDRO underlay)
approx. 22 dB (thanks to ECO SOUND HYDRO underlay)
approx. 22 db (thanks to LCO SOOND ITT DKO underlay)

BALANCE | WOOD EDITION | OVERSIZE BALANCE | STONE EDITION | OVERSIZE

class 33	class 33
7.5 mm, 0.29 in.	7.5 mm, 0.29 in.
244 mm, 9.60 in.	
1845 mm, 72.63 in.	1380 mm, 54.33 in.
2.25 m², 24.22 sqft	2.75 m², 29.60 sqft
20.78 kg, 45.81 lbs	19.86 kg, 43.39 lbs
960 kg, 2116 lbs	740 kg, 1631 lbs
limited lifetime	limited lifetime
Soft Shield	Soft Shield
for example: floor, kitchen, living room, home office, bathroom	for example: floor, kitchen, living room, home office, bathroom
for example: classroom, offices, stores	for example: classroom, offices, stores
100% waterproof	100% waterproof
20 x 20 m, 65 x 65 ft (using state of the art technology)	20 x 20 m, 65 x 65 ft (using state of the art technology)
-34°C to +70°C, -30°F to +160°F	-34°C to +70°C, -30°F to +160°F
V-groove 4 sided	V-groove 4 sided
B _f -s1, flame retardant, no/low smoke emission	B _{fi} -s1, flame retardant, no/low smoke emission
embedded (liquid based) radiant floor heating	embedded (liquid based) radiant floor heating
max. 0.1 (m2K)/W	max. 0.1 (m2K)/W
≤ 2 kV	≤ 2 kV
Class E1/2020, under detection limit (CARB2/TSCA VI compliant)	Class E1/2020, under detection limit (CARB2/TSCA VI compliant)
DS	DS
R10	R10
IP ≥ 8000, class 34	IP ≥ 8000, class 34
MSR-A1	MSR-A1
> 1800 mm, 70.86", class 34	> 1800 mm, 70.86", class 34
≤ 0.15 mm/ 0.005 in.	≤ 0.15 mm/ 0.005 in.
No visible change (aceton, coffee, hydrogen peroxide)	No visible change (aceton, coffee, hydrogen peroxide)
3x higher than Class 34 (11.28 kN/m)	3x higher than Class 34 (11.28 kN/m)
4 points, matt oiled look	4 points, matt oiled look
light fast, ≥ 6	light fast, ≥ 6
25,000 cycles without any damage	25,000 cycles without any damage
yes, highly resistant	yes, highly resistant
antibacterial	antibacterial
VOC A+, agBB schema, Floorscore, Greenguard Gold	VOC A+, agBB schema, Floorscore, Greenguard Gold
Core Board more than 50 %	Core Board more than 50 %
yes	yes
pass (>0.25 ppm)	pass (>0.25 ppm)
1 mm ECO SOUND HYDRO	1 mm ECO SOUND HYDRO
approx. 68 dB (thanks to ECO SOUND HYDRO underlay)	approx. 68 dB (thanks to ECO SOUND HYDRO underlay)
approx. 63 dB (thanks to ECO SOUND HYDRO underlay)	approx. 63 dB (thanks to ECO SOUND HYDRO underlay)
approx 22 dB (thanks to ECO SOLIND HYDRO underlay)	approx 22 dB (thanks to ECO SOLIND HYDRO underlay)

FACTS

ESSENCE

class of usage		EN 16511:2019
thickness		EN 16511:2019
width		EN 16511:2019
length		EN 16511:2019
pcs/box		
surface area per box		
box/pallet		
weight/box		
weight/pallet		
warranty residential (as per separate w https://www.corepel.com/en/service/		
warranty commercial (as per separate https://www.corepel.com/en/service/		
surface layer		
unique plank design		
domestic usage interior use		
commercial usage interior use		
waterproof		
type of installation		
surface without transition moldings		
post installation temperature range		
type of edge		
reaction to fire	CE	EN 13501:2010
floor heating	CE	
thermal resistance	CE	
antistatic	CE	EN 1815:2011
formaldehyde emission	CE	EN 717-1:2005
slip resistance	CE	EN 14041:2008
slip resistance	CE	DIN 51130:2014
abrasion resistance (falling-sand meth	od)	EN 16511:2019
micro-scrartch resistance		EN 16511:2019
impact resistance large ball		EN 16511:2019
resistance to indentation		ISO 24343-1:2012
stain resistance		EN 438-2:2019
strength of joint (short side/long side)		ISO 24334:2019
gloss level		
light fastness		EN 20105:1995
castor chair resistance		EN 425:2002
burning cigarette		EN 1399:1998
antibacterial resistance		ISO 22196:2011
sustainable certification		
VOC emission		ISO 16000
natural wood fiber content		
PVC free		
Phthalates free		
heavy metal content		ASTM F963
attached underlayment		
impact sound transmission		ASTM E492 IIC
airborne sound transmission		ASTM E492 IIC ASTM E90 (STC)
		ASTM E90 (STC)
effectiveness of floor coverings in reducing impact sound transmission		(Delta IIC)

BALANCE | WOOD EDITION | OVERSIZE+

class 33
5.5 mm, 0.21 in.
1380 mm, 54.33 in.
10
2.69 m², 28.96 sqft
40
17.38 kg, 38.32 lbs
720 kg, 1587 lbs
limited lifetime
Soft Shield
10
for example: floor, kitchen, living room, home office, bathroom
for example: classroom, offices, stores
100% waterproof
20 x 20 m, 65 x 65 ft (using state of the art technology)
-34°C to +70°C, -30°F to +160°F
V-groove 4 sided
B _{fi} -s1, flame retardant, no/low smoke emission
embedded (liquid based) radiant floor heating
max. 0.1 (m2K)/W
≤2 kV
Class E1/2020, under detection limit (CARB2/TSCA VI compliant)
DS
R10
IP ≥ 8000, class 34
MSR-A1
> 1800 mm/ 70.86 in., class 34
≤ 0.15 mm/ 0.005 in.
No visible change (aceton, coffee, hydrogen peroxide)
3x higher than Class 34 (11.28 kN/m)
4 points, matt oiled look
light fast, ≥ 6
25,000 cycles without any damage
yes, highly resistant
antibacterial
FSC mix
VOC A+, agBB schema, Floorscore, Greenguard Gold
Core Board more than 50 %
yes
yes pass (>0.25 ppm)
1 mm ECO SOUND HYDRO
approx. 68 dB (thanks to ECO SOUND HYDRO underlay)
approx. 63 dB (thanks to ECO SOUND HYDRO underlay)
approx. 22 dB (thanks to ECO SOUND HYDRO underlay)

BALANCE | WOOD EDITION | OVERSIZE+

class 33
5.5 mm, 0.21 in.
195 mm, 7.67 in.
1380 mm, 54.33 in.
10
2.69 m², 28.96 sqft
40
17.38 kg, 38.32 lbs
720 kg, 1587 lbs
limited lifetime
5 years
Soft Shield
10
for example: floor, kitchen, living room, home office, bathroom
for example: classroom, offices, stores
100% waterproof
20 x 20 m, 65 x 65 ft (using state of the art technology)
-34°C to +70°C, -30°F to +160°F
V-groove 4 sided
B _n -s1, flame retardant, no/low smoke emission
embedded (liquid based) radiant floor heating
max. 0.1 (m2K)/W
≤2 kV
Class E1/2020, under detection limit (CARB2/TSCA VI compliant)
DS
RIO
IP ≥ 8000, class 34
MSR-A1
> 1800 mm/ 70.86 in., class 34
≤ 0.15 mm/ 0.005 in.
No visible change (aceton, coffee, hydrogen peroxide)
3x higher than Class 34 (11.28 kN/m)
4 points, matt oiled look
light fast, ≥ 6
25,000 cycles without any damage
yes, highly resistant
antibacterial
FSC mix
VOC A+, agBB schema, Floorscore, Greenguard Gold
Core Board more than 50 %
yes
yes
pass (>0.25 ppm)
1 mm ECO SOUND HYDRO
approx. 68 dB (thanks to ECO SOUND HYDRO underlay)
approx. 63 dB (thanks to ECO SOUND HYDRO underlay)
approx 22 dB (thanks to ECO SOUND HYDRO underlay)

*tost cortificatos available at coronal c