
SSP MAX



The **Superspotter Max** (SSP MAX) is the latest Almex spot and rip repair press for heavyweight rubber belt maintenance. Use these presses to repair small tears and punctures in the field or shop.

The SSP MAX comes with 305 mm x 305 mm (12" x 12") platens, 7 kg/cm² (100 PSI) and 2 sizes suitable for 1500 mm (60") and 2000 mm (78") belt width.













ALMEX GROUP | Shaw Almex Industries Ltd.
1.800.977.5423 sales@almex.com

Shaw Almex Europe B.V.
31 646648648
Drachten, The Netherlands

Shaw-Almex Industries
1 905 643 7750
Stoney Creek, Ontario

Shaw-Almex Industries
1 705 746 5884
Parry Sound, Ontario

Shaw-Almex Fusion, LLC.
1 404 292 8600
Decatur, Georgia, USA

Shaw Almex Africa (Pty) Ltd.
27 11 794 8262
South Africa

www.almex.com

FEATURES:


- A Lightweight, Strong and Portable Aluminum Frame:
- Lighter frame than the traditional Superspotter (~5%)
- Convenient handles on the frame and upper platen
- 3 lift hooks on the top handle for positioning in the field
- Maximum Belt Width SSP MAX 1.5M: 1500 mm| 60”
- Maximum Belt Width SSP Max 2M: 2000 mm | 78”

- Reliable Pressure and Heating controls
- Dual voltage 110V- 220 V
- Quick connect air connector
- Unique air spring actuator pressure system for quick, even pressure inflation
- P.I.D temperature controller reaches set point
- Pressure safety valve also aids in pressure deflation
- In frame controls for pressure and cooling
- Durable expanded graphite heating element that heats up in less time; 220V will heat to splicing temperature in 10 minutes
- SSP MAX is CE Certified

- Quality Almex 305 mm x 305 mm (12” x 12”) platens:
- Custom “Extruded Plank” fast cooling system within platens
- Platens swivel to 45 degrees
- 65 mm (2 ½”) of Daylight Opening
- Removable platens with carry case for ease of transportation

OPTIONS:

- 1500 mm or 2000 mm maximum belt width
- Inframe Controls can be left out, and an external control box may be used (i.e. T2, T6)
- Custom graphic panels available on request
- Ground Fault unit available on request
- Ability to link multiple SSP MAX frames to utilize a longer platen for rips, available as a custom order on request



SSP MAX 1.5M

SPECIFICATIONS

SSP MAX 2M

SSP-MAX-1212-60	Metric	Imperial
Press Length	1190 mm	46 3/4”
Press Throat Length	776 mm	30 9/16”
Press Width	317.5 mm	12 1/2”
Press Height	686 mm	27”
Platen Dimensions	305 mm x 305 mm	12” x 12”
Platen Carry Case Dimensions	818 mm x 530 mm x 333mm	32 1/4” x 21 x 13 1/4
Platen Carry Case Weight	11.5 kg	25 lbs
Frame Weight	20 kg	45 lbs
Press Weight (Platens Removed)	23 kg	50 lbs
Total Platen Weight	22 kg	48 lbs
Total Press Weight	45 kg	98 lbs

SSP-MAX-1212-78	Metric	Imperial
Press Length	1470 mm	57 7/8”
Press Throat Length	1010 mm	39 3/4”
Press Width	317.5 mm	12 1/2”
Press Height	710 mm	28 3/4”
Platen Dimensions	305 mm x 305 mm	12” x 12”
Platen Carry Case Dimensions	818 mm x 530 mm x 333mm	32 1/4” x 21 x 13 1/4
Platen Carry Case Weight	11.5 kg	25 kg
Frame Weight	41 kg	90 lbs
Press Weight (Platens Removed)	43 kg	95 kg
Total Platen Weight	22 kg	48 lbs
Total Press Weight	65 kg	143 lbs

ALMEX GROUP | Shaw Almex Industries Ltd.
1.800.977.5423 sales@almex.com

Shaw Almex Europe B.V.
31 646648648
Drachten, The Netherlands

Shaw-Almex Industries
1 905 643 7750
Stoney Creek, Ontario

Shaw-Almex Industries
1 705 746 5884
Parry Sound, Ontario

Shaw-Almex Fusion, LLC.
1 404 292 8600
Decatur, Georgia, USA

Shaw Almex Africa (Pty) Ltd.
27 11 794 8262
South Africa

www.almex.com