





MODEL ATM FINGER PUNCH



Machinery for preparation of PVC/PU Conveyor Belts

- Manually operated, light and easy to handle. Lower weight, with aluminum frame with removable head.
- Open construction. Open ends make it possible to punch wider belts.
- Integrated clamping bar. Excellent adjustment of the belt for a perfect punch.
- Finger-over-finger without the need to move the belt.

Material	• Aluminum	
Press	• Manual	
Pressure area	• 90 x 60 (4 x 2.3)	
Cutting Board	• 50 x 20 (2 x .75)	• 50 x 20 (30") (2 x .80)
	• 80 x 20 (3 x .75)	• Any other upon request
	• 70 x 12 (2.75 x .50)	

Model	Weight in Kg, (lbs)			Dimensions in mm, (inches)		
	Head	Structure	Total	Height	Length	Width
ATM 300	6.8 (15)	12.7 (28)	19.5 (43)	241 (9.5)	580 (23)	390 (15)
ATM 600	6.8 (15)	13.7 (30)	20.5 (45)	241 (9.5)	880 (35)	390 (15)
ATM 800	6.8 (15)	14.7 (32)	21.5 (47)	241 (9.5)	1080 (42)	390 (15)
ATM 1000	6.8 (15)	15.7 (34)	22.5 (50)	241 (9.5)	1280 (50)	390 (15)

Dimensions and weights are approximate and they are subject to changes without notice.

FOR THIS PRODUCT AND ALL YOUR OTHER CONVEYOR BELT NEEDS CONTACT:

SHAW ALMEX INDUSTRIES LTD.

Canada: 1-800-461-4351, USA: 800-977-5423

VISIT US ON THE WEB

www.almex.com

Fingerpunch

MODEL	BELT WIDTH		FINGER SIZES		DIMENSIONS (L x W x H)		TOTAL WEIGHT	
	IN	MM	IN	MM	IN	MM	LBS	KG
ATM-300-50-20	12	300	2x.75	50x20	23x15x9.5	580x390x240	43	20
ATM-300-50-20-30 * (bias)	12	300	2x.75	50x20	23x15x9.5	580x390x240	43	20
ATM-300-80-20	12	300	3x.75	80x20	23x15x9.5	580x390x240	43	20
ATM-300-70-12	12	300	2.75x.5	70x12	23x15x9.5	580x390x240	43	20
ATM-600-50-20	24	600	2x.75	50x20	35x15x9.5	880x390x240	45	21
ATM-600-50-20-30 * (bias)	24	600	2x.75	50x20	35x15x9.5	880x390x240	45	21
ATM-600-80-20	24	600	3x.75	80x20	35x15x9.5	880x390x240	45	21
ATM-600-70-12	24	600	2.75x.5	70x12	35x15x9.5	880x390x240	45	21
ATM-800-50-20	32	800	2x.75	50x20	42x15x9.5	1080x390x240	47	22
ATM-800-50-20-30 * (bias)	32	800	2x.75	50x20	42x15x9.5	1080x390x240	47	22
ATM-800-80-20	32	800	3x.75	80x20	42x15x9.5	1080x390x240	47	22
ATM-800-70-12	32	800	2.75x.5	70x12	42x15x9.5	1080x390x240	47	22
ATM-1000-50-20	40	1000	2x.75	50x20	50x15x9.5	1280x390x240	50	23
ATM-1000-50-20-30 * (bias)	40	1000	2x.75	50x20	50x15x9.5	1280x390x240	50	23
ATM-1000-80-20	40	1000	3x.75	80x20	50x15x9.5	1280x390x240	50	23
ATM-1000-70-12	40	1000	2.75x.5	70x12	50x15x9.5	1280x390x240	50	23

* 30 deg bias

Specifications are approximate and subject to change without notice.