



MSHA CS-21 FABRIC BELT TIE GUM



Almex 48601 MSHA Grade Fabric Belt Tie Gum is an uncured rubber for hot vulcanized belt splicing. It is designed for use as a skim rubber replacement material in splicing MSHA Grade fabric conveyor belts. This material is designed to be used in both finger and step splices of MSHA Grade fabric conveyor belts.

FEATURES

- Enhances the working life of MSHA Grade fabric belt splices
- Improves flexibility and strength of MSHA Grade conveyor belt splices
- Eliminates surface contamination (normal application) with double sided poly
- Uses poly colour coding system to ID compound

MSHA CS-21 FABRIC BELT TIE GUM

PRODUCT CODE	POLY COLOR BOTH SIDES	THICKNESS/GAUGE			WIDTH		LENGTH		ROLL WEIGHT	
		FRAC	MM	IN	MM	IN	M	FT	KG	LB
AA-FBGMSHA-030	Orange	-	.7	.030	.5	20	15	50	7.4	16.3
AA-FBGMSHA-040	Orange	-	1	.040	.5	20	15	50	10.6	23.3
AA-FBGMSHA-060	Orange	-	1.5	.060	.5	20	15	50	15.9	34.9

MSHA CS-21 FABRIC BELT TIE GUM PROPERTIES	
Rubber Color	Black
Poly Liner Color	Orange (double-sided)
Base Polymer	SBR/BR Rubber
Specific Gravity	1.39 - 1.43
Hardness	57 - 67 Shore A
Rubber Tensile	1450 - 1700 psi
Rubber Elongation	500 - 700% (at break)
Shelf Life	6 Months at 70 °F (21 °C) or 12 Months at 50 °F (10 °C)



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.