



POWER-TILT

Road Construction

Civils

Landscaping

Waterways Work

Rail Work

Golf Course Construction

Demolition

Forestry

- Range of tilting couplers to suit excavators from 1 – 50 tonnes
- Up to 180 degrees of tilt
- Narrow and compact – use with all attachments including narrowest trenching buckets
- Built in quick coupler to suit OEM or dedicated bucket systems
- No exposed moving parts
- Manufactured using high grade structural and wear resistant steels for exceptional durability
- Built in relief valve provides hydraulic overload protection

“Perfect Partners”



Exac-One Ltd
The Mount Buildings
Upton on Severn
Worcs
WR8 0QL
United Kingdom

Tel: +44(0)1684 593052
Fax: +44(0)1684 592249
info@exac-one.co.uk
www.exac-one.co.uk
April 2014

Powertilt Technical

		4.5	6N	6W	7	8	9	10	11	12
Carrier weight up to	(t)	2.0	3.8	4.8	6.8	9.1	14	20	27	34
Weight	kg	40	75	85	145	195	260	385	545	680
Max Pressure	bar	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Oil Flow	l/m	2-4	3-6	3-6	6-12	12-20	24-28	24-32	32-44	36-52
Max tilt angle	°	180	180	180	180	180	134	134	134	134