FOREST RESIDUE GRAB



Green Waste Handling

Timber Handling

Forestry & industrial Applications

Loading and Sorting

- Range of waste grabs to suit excavators and loaders from 2.0 to 18 tonnes
- Manufactured using high grade structural and wear-resistant steels, for exceptional durability
- Jaw design gives excellent penetration into stacked timber
- Single central cylinder with integral check valve ensures load holding even in the event of hose failure
- Simple/ Durable/ Reliable
- Available with Rotator Options

"Perfect Partners"

Exac-One Ltd
The Mount Buildings
Upton on Severn
Worcs
WR8 0QL
United Kingdom

Tel: +44(0)1684 593052
Fax: +44(0)1684 592249
info@exac-one.co.uk
www.exac-one.co.uk
April 2014

Forest Residue Grab Technical

		PTO-300/SC	PTO-400/SC	PTO-550/SC
Carrier Weight	tonnes	2-5	6-10	11-18
Weight	kg	200	350	550
Max Pressure	bar	220	220	300
Maximum Load	DaN	2000	2500	4000
Dimension “A”	mm	85	110	115
Dimension “B”	mm	590	630	780
Dimension “C”	mm	775	830	1050
Dimension “D”	mm	1600	1900	2150
Dimension “E”	mm	425	520	600
Dimension “G”	mm	850	985	1120

