



FUSION COMBI SCRAPER 85/55/85



Fusion Combi 85/55/85 is a vulcanized laminate of two hard outer layers, containing a softer inside grey layer. Perfect for larger sticky applications.

FEATURES

- Twice the wear life of commercial SBR rubber
- Produced with the finest natural rubber
- Multi-layer construction provides long wear life with excellent cleaning capabilities
- Hard outside layers provide impact protection
- Soft inside layer provides superior squeegee type cleaning

FUSION COMBI SCRAPER 85/55/85

PRODUCT CODE	THICKNESS/GAUGE		WIDTH		ROLL LENGTH		ROLL WEIGHT	
	MM	IN	M	IN	M	FT	KG	LBS
CCR-8555-7506	20	.75	150	6	15.25	50	40	88
CCR-8555-7508	20	.75	200	8	15.25	50	50	111
CCR-8555-755950	20	.75	1500	59	15.25	50	338	854
CCR-8555-1006	25	1	150	6	15.25	50	49	107
CCR-8555-1008	25	1	200	8	15.25	50	63	138
CCR-8555-105950	25	1	1500	59	15.25	50	413	910
CCR-8555-1506	40	1.5	150	6	5	50	20	45
CCR-8555-1508	40	1.5	200	8	5	50	26	57
CCR-8555-155950	40	1.5	1500	59	5	50	239	525
CCR-8555-2006	50	2	150	6	5	50	43	95
CCR-8555-2008	50	2	200	8	5	50	35	76
CCR-8555-205950	50	2	1500	59	5	50	319	700

FUSION COMBI SCRAPER 85/55/85 PROPERTIES		
Colour	Black	Grey
Elastomer	SBR	SBR
Tensile Strength	19.5 Mpa	15 Mpa
Elongation at Break	400%	530%
Density	1.17 g / cm ³	1.1 g / cm ³
Hardness	85 Shore A	55 Shore A
Abrasion Resistance	100 mm ³	160 mm ³



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.