



MINI-MOWER

Vegetation Control
Site Clearance
Thinning Operations
Embankment Maintenance
Hedges, Scrub, Grass
Boundary Restoration
Woodland Maintenance

- To suit excavators from 1 – 12 tonne (std configuration) also available for loaders and skid steers
- Cut capability for grass and vegetation up to 90mm diameter
- Manufactured using high grade structural and wear resistant steels, for exceptional strength and durability.
- Adjustable rear roller
- Choice of flails (does not apply to DXL models)
- Options – floating link, flow control valve, jack stand

“Perfect Partners”



The Attachment Specialist

Exac-One Ltd
The Mount Buildings
Upton on Severn
Worcs
WR8 0QL
United Kingdom

Tel: +44(0)1684 593052
Fax: +44(0)1684 592249
info@exac-one.co.uk
www.exac-one.co.uk
May 2016

Mini Mower Technical

		TE60 DXL	TE80 DXL	TE80 DL	TE100 DL	TE80 DP	TE100 DP	TE120 DP	TE100 CL	TE120 CL
Excavator Weight Range	t	1-2	1.5-2.5	2-3.5	2.5-4	2.5-5	2.5-5	4-8	6-9	6-9
Mulcher Weight w/o Bracket	kg	70	85	100	120	170	195	230	315	345
Oil flow requirement	l/min	20-30	20-30	30-45	30-50	30-50	40-60	50-70	60-70	60-70
Max Hyd Circuit pressure	bar	160	160	170	170	180	180	180	190-200	190-200
Cut width	mm	600	800	800	1000	800	1000	1200	1050	1250
Max cut diameter	mm	10	10	50	50	50	50	50	70	70
Total Width	mm	800	1000	1000	1150	1100	1300	1500	1250	1400