



# ECRF COLD FUSION CEMENT & HARDENER



Photo shows 800 ml / .25 gal cement with 35 gr / 1.2 oz hardener.

ECRF is the ideal cement for conveyor belt repair and splicing, and is excellent for use on wood, fiberglass, concrete, urethane, steel, rubber and fabric.

## FEATURES

- ECRF is an ethyl acetate based chloroprene cement, and is available in four sizes
- Free of chlorinated hydrocarbons
- High initial and permanent adhesion
- Easy to process
- Offers higher threshold limit values than for chlorinated hydrocarbons
- Flammable

## ECRF HARDENER

PRODUCT CODE	GRAM	OUNCE
CH-ECRF-018	18	.63
CH-ECRF-035	35	1.2

## ECRF COLD BOND CEMENT

PRODUCT CODE	VOLUME		WEIGHT		COVERAGE		HARDENER BOTTLE QUANTITY
	LITER	GAL	KG	LBS	M <sup>2</sup>	FT <sup>2</sup>	
CC-ECRF-001	.4	.12	.35	.8	1.4	15	1 CH-ECRF-018
CC-ECRF-002	.8	.20	.7	1.5	2.8	30	1 CH-ECRF-035
CC-ECRF-010	4	1	3.5	7.7	14	150	5 CH-ECRF-035
CC-ECRF-200	200	50	175	386	695	7500	250 CH-ECRF-035

ECRF PROPERTIES	
Colour	Black
Pot Life	4 Hours @ 21 °C / 70 °F
Working Temperature	-23 °C to 82 °C / -10 °F to 180 °F
Shelf Life	24 months in a cool, dark location



**Note:** The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.