



MAXI-FOREST

Vegetation Control

Site Clearance

Thinning Operations

Embankment Maintenance

Whole Trees, Scrub, Grass

Boundary Restoration

Woodland Maintenance

- Available with **Drum Rotor** or **Fixed Tool Rotor**
- To suit excavators from 18 tonnes to 25 tonnes (std configuration) also available for tractors , loaders and skid steers
- Cut capability for grass and vegetation up to 300mm diameter (350mm diameter for fixed tool rotor)
- Heavy duty casing manufactured from Weldom 700 steel for maximum strength and durability.
- Internal frame and counter blades manufactured from Hardox 400
- Piston motor gives optimum power output.
- Multi-belt transmission
- Hydraulic operation of front cover

“Perfect Partners”



The Attachment Specialist

Exac-One Ltd
The Mount Buildings
Upton on Severn
Worcs
WR8 0QL
United Kingdom

Tel: +44(0)1684 593052
Fax: +44(0)1684 592249
info@exac-one.co.uk
www.exac-one.co.uk
May 2016

Technical Drum Rotor

		TF 130 S	TF 160 S
Excavator Weight Range	tonnes	18-21	21-25
Mulcher Weight w/o Bracket	kg	1290	1450
Oil flow requirement	l/min	130-150	130-150
Max Hyd Circuit pressure	bar	250-270	250-270
Cut width	mm	1300	1600
Max cut diameter	mm	300	300
Rotor type		Drum Rotor	Drum Rotor
Standard motor size	cc	64	64
Total Width	mm	1500	1800

Fixed Tool Rotor

		TF 130 S UX	TF 160 S UX
Excavator Weight Range	tonnes	18-25	21-25
Mulcher Weight w/o Bracket	kg	1370	1540
Oil flow requirement	l/min	170-180	180-200
Max Hyd Circuit pressure	bar	270-300	270-300
Cut width	mm	1300	1600
Max cut diameter	mm	450	450
Rotor type		Fixed Tool	Fixed Tool
Standard motor size	cc	84	84
Total Width	mm	1500	1800