



Split Oversize Timber

Split Tree Stumps

Split Tree Roots

Convert Waste Timber Into Fuel Wood

Handle Timber

- Unique cone design ensures optimum splitting performance with minimum power requirement.
- Powered from excavator's double-acting auxiliary circuit.
- Manufactured using high-grade structural and wear-resistant steels for exceptional durability.
- The Black-Splitter can be used for timber handling and processing operations.
- To suit excavators from 1.5t 25t; also suitable for loaders, skid steers and telehandlers.
- Two piece cone with replaceable tip.
- Modular design with adaptable mounting interface to suit excavators and loaders.
- 12 months warranty.

"Perfect Partners"



Exac-One Ltd
The Mount Buildings
Upton on Severn
Worcs
WR8 0QL
United Kingdom

Tel: +44(0)1684 593052 Fax: +44(0)1684 592249 info@exac-one.co.uk www.exac-one.co.uk April 2014

Black-Splitter Technical

		S2500	S2630	SG1 630	S2X800+	S2G
Cone Diameter (Std)	mm	200	200	200	245	300
Weight (Approx)	Kgs	119	122	172	161	400
Carrier Weight	t	1.5-3	1.5-6	2-6	5-14	10-25
Oil Pressure	Bar	180-250	180-230	180-230	180-380	180-380
Oil Flow Requirement	l/Min	25+	25+	25+	45+	75+





