

BEAR-CLAW

Grab & Cut Multiple Stems

Boundary Restoration

Tree Pruning

Woodland Maintenance

Thinning and Coppicing

- Range of 'Shear-Grabs' to suit excavators and loaders from 2.5 to 25.00 tonnes
- Holds Timber Throughout Cutting Process
- Designed and built in Finland.
- Replaceable Blade
- Manufactured using high grade structural and wear resistant steels, for exceptional durability
- Tilt option available
- 'Delimiting Jaw' option available (removes small branches prior to cutting the tree – also scrapes bark which aids drying)
- 'Thicket Clearing Blade' option for multiple small stems
- 'Accumulator Grab' option on some models

"Perfect Partners"



The Attachment Specialist

Exac-One Ltd
 The Mount Buildings
 Upton on Severn
 Worcs
 WR8 0QL
 United Kingdom

Tel: +44(0)1684 593052
 Fax: +44(0)1684 592249
 info@exac-one.co.uk
 www.exac-one.co.uk
 Jan 2016

Bear Claw Technical

| | | BC13 | BC19 | BC25BB | BC25 | BC35 |
|--------------------------|--------|------|---------|----------|-----------|-----------|
| Excavator Weight Range | Tonnes | 2.5 | 4.0-8.0 | 8.0-15.0 | 13.0-20.0 | 15.0-25.0 |
| Weight | Kg | 125 | 260 | 330 | 470 | 700 |
| Maximum Cut Diameter | mm | 170 | 230 | 270 | 270 | 340 |
| Max Opening Width | mm | 750 | 1000 | 700 | 1350 | 1550 |
| Blade Thickness | mm | 10 | 10 | 12 | 12 | 16 |
| Oil Flow Minimum | l/m | 30 | 40 | 50 | 60 | 70 |
| Maximum Circuit Pressure | Bar | 250 | 250 | 250 | 250 | 250 |



BC25BB



BC35



BC25