

# MINI-HAMMER

**Break Concrete**

**Break Rock**

**Drive posts**

**Pile Driving**

- Range of breakers to suit excavators from 0.7 – 10 tonnes
- Mini-Hammer range designed and built in the UK
- Compact and powerful, suitable for a wide variety of applications
- Options – choice of tools, post driving kit, lower mounting position
- Simple, strong design, without tie-rods
- Low maintenance
- Noise and vibration suppressed

**“Perfect Partners”**



**The Attachment Specialist**

Exac-One Ltd  
 The Mount Buildings  
 Upton on Severn  
 Worcs  
 WR8 0QL  
 United Kingdom

Tel: +44(0)1684 593052  
 Fax: +44(0)1684 592249  
 info@exac-one.co.uk  
 www.exac-one.co.uk  
 Nov 2017

## Mini Hammer Technical

		MH 40	MH 45	MH 55	MH 65	MH70	MH 75	MH80
Carrier weight		0.7-1.5	1.5-2.8	2.8-4.0	4.0-5.5	5.0-7.0	6.5-8.5	7.0-10
Weight	kg	85	120	135	190	210	305	375
Oil flow requirement	l/min	14-30	25-45	40-60	45-70	55-80	70-100	80-110
Operating pressure	bar	120	90	110	110	110	120	120
Impact Rate	bpm	650-1100	650-1100	700-1250	550-1200	650-1400	650-1400	550-1200
Impact Energy	joules	260	550	680	850	800	1100	1400
Tool Diameter	mm	40	45	55	65	70	75	80
Overall Length	mm	1180	1180	1300	1450	1500	1600	1650