



FUSION STRIPLAGG URDS



Fusion StripLagg URDS (unique triangular pattern) is a small or large profile pulley lagging, ideal for driven pulleys with medium to very high tension & belt ratings.

FEATURES

- Fusion StripLagg URDS is designed to be applied to the pulley with the grooves in the lagging running horizontal to the pulley face
- The profile pattern provides effective surface contact with the conveyor belt
- The open area or spacing between the profiles effectively removes product fines, moisture and water when present on the system
- Positive belt traction, creating exceptional wear life
- Easy to install
- Improved belt tracking
- Better system up-time creating lower costs
- Universal rubber sheet offers little or no waste
- Large aggressive diamond profile material provided in 12" wide strips

FUSION STRIPLAGG URDS

PRODUCT CODE	THICKNESS/GAUGE		WIDTH		LENGTH		ROLL WEIGHT	
	MM	IN	MM	IN	M	FT	KG	LB
FL-SURDS-5050	12	.5	304.8	12	15.25	50	61	134
FL-SURDS-5850	15	.675	304.8	12	15.25	50	76	168
FL-SURDS-7550	19	.75	304.8	12	12.2	40	77	170
FL-SURDS-0150	25	1	304.8	12	10	33	85	184

* Small diamond available in 304.8 mm (.5")

FUSION STRIPLAGG URDS PROPERTIES			
Colour		Black	
Elastomer		NR/BR	
Tensile Strength		20 Mpa	2700 psi
Elongation at Break		500%	DIN 53504
Density		1.12 g / cm ³	DIN 53050
Hardness		60 (±5) Shore A	DIN 53505
Abrasion Resistance		<105 mm ³	DIN 53516



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.