



VORTEX

AIR SERIES VULCANIZING PRESS



The Vortex Air Cooled Press is a unified press assembly designed to splice PVC and PU lightweight belting in a continuous cycle. Set the temperature, time, pressure and simply push the button.

FEATURES

- All-In-One
- Lightweight aluminum construction
- Press accommodates belt widths 400 mm / 16" to 1500 mm / 60"
- Low profile height: 200 mm / 8" high
- Temperature up to 200 deg C (392 deg F)
- Operating Pressure 2.1 KG/CM2 / 30 PSI
- Available in 110 or 220 volt single phase
- VX-1310 and VX-1610 also available in 460 Volt 3 phase

VORTEX SPECIFICATIONS

MODEL	PLATEN SIZE		MAXIMUM BELT WIDTH		OVERALL LENGTH		OVERALL WIDTH		OVERALL HEIGHT		TOTAL WEIGHTH	
	MM	IN	MM	IN	MM	IN	MM	IN	MM	IN	KG	LB
VX 510	160 X 510	6 X 20	455	18	585	23	230	9	205	8	27	59
VX 710	160 X 710	6 X 28	660	26	785	31	230	9	205	8	35	76
VX 910	160 X 910	6 X 36	865	34	990	39	230	9	205	8	42	92
VX 1110	160 X 1110	6 X 44	1065	42	1195	47	230	9	205	8	49	109
VX 1310	160 X 1310	6 X 51	1245	49	1395	55	230	9	205	8	57	126
VX 1610	160 X 1610	6 X 63	1525	60	1675	66	230	9	205	8	68	150



Note: The above data is based on extensive testing and represents standard values. Shaw Almix Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

<p>MODEL – VORTEX</p> <p>6 inch (160 mm) Platen</p>		<p>Maximum operating pressure 30 psi (2.2 kg/cm²)</p> <p>Maximum temperature 392 deg F (200 deg C)</p>
--	--	---

MODEL	PLATEN SIZE		MAXIMUM BELT WIDTH		OVERALL LENGTH		DIMENSION A		DIMENSION B		DIMENSION C		DIMENSION D		TOTAL WEIGHT	
	INCH	MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM
VX-510	6 x 20	160 x 510	18	455	23	585	3.3	84	4.6	118	8	205	9	230	59	27
VX-710	6 x 28	160 x 710	26	660	31	785	3.3	84	4.6	118	8	205	9	230	76	35
VX-910	6 x 36	160 x 910	34	865	39	990	3.3	84	4.6	118	8	205	9	230	92	42
VX-1110	6 x 44	160 x 1110	42	1065	47	1195	3.3	84	4.6	118	8	205	9	230	109	49
VX-1310	6 x 51	160 x 1310	49	1245	55	1395	3.3	84	4.6	118	8	205	9	230	126	57
VX-1610	6 x 63	160 x 1610	60	1525	66	1675	3.3	84	4.6	118	8	205	9	230	150	68

Specifications are approximate and subject to change without notice.